



PROPRIETARY DOCUMENT
SIMPLIFIED DRAWING
SEE NOTE 8

NOTES:

1. PRODUCT TYPE: SELF RESTORING SHUTTER MECHANISM.
2. MAXIMUM OPERATING VOLTAGE: 3.3 VDC.
3. MAXIMUM PULL IN VOLTAGE: 2.5 VDC @ 25 °C.
4. MINIMUM DROP OUT VOLTAGE: .5 VDC @ 25 °C.
5. COIL RESISTANCE: 12 OHMS ±10% @ 25 °C. LEADS SHALL BE RED (+) BLACK (-)TEFLON INSULATED WIRE PER M16878 TYPE 30 ET 6" LONG MINIMUM AND STRIPPED 1/4" ± 1/8" BOTH ENDS.
6. ROTATION: 40° ± 2° CW, WHEN ENERGIZED.
7. BLACK ANODIZE SHUTTER AND HOUSING.
8. THIS DRAWING PROVIDES GENERAL PRODUCT INFORMATION. FOR COMPLETE TECHNICAL DETAILS PLEASE CONTACT US AT (203) 544-9341 OR VIA EMAIL AT SALES@BRANDSTROMINSTRUMENTS.COM.

COPYRIGHT © 2010 BRANDSTROM INSTRUMENTS, INC. ALL RIGHTS RESERVED.

DIMENSION TOLERANCES UNLESS OTHERWISE SPECIFIED			
ANGLES	± 1°	2 PLACES	±.010
FRACTIONS	± 1/32	3 PLACES	±.005
	1 PLACE	4 PLACES	±.0005
MATERIAL:	N/A		DRAWN:
FINISH:	N/A		CHECKED:
DATE:	SCALE:	NONE	
TITLE:	DWG NO:	SHEET:	REV:
SHUTTER ASSEMBLY	A1058	1 of 1	

