


PROPRIETARY DOCUMENT
SIMPLIFIED DRAWING
 SEE NOTE 7



NOTES:

1. NORMAL OPERATING VOLTAGE: 5.0 VDC .
2. MAXIMUM PULL IN VOLTAGE: 4.5 VDC @ 25 °C.
3. MINIMUM DROP OUT VOLTAGE: 0.5 VDC @ 25 °C.
4. COIL RESISTANCE: 75 OHMS $\pm 10\%$ @ 25 °C. LEADS SHALL BE RED (+) BLACK (-) TEFLON INSULATED WIRE PER M16878 TYPE 32 ET 6" LONG MINIMUM AND STRIPPED 1/4" $\pm 1/8$ " BOTH ENDS.
5. ROTATION: $32.5^\circ \pm 2^\circ$ CCW, WHEN ENERGIZED, AS VIEWED FROM SHUTTER END.
6. BLACK ANODIZE SHUTTER AND HOUSING.
7. THIS DRAWING PROVIDES GENERAL PRODUCT INFORMATION. FOR COMPLETE TECHNICAL DETAILS PLEASE CONTACT US AT (203) 544-9341 OR VIA EMAIL AT SALES@BRANDSTROMINSTRUMENTS.COM.

COPYRIGHT © 2010 BRANDSTROM INSTRUMENTS, INC. ALL RIGHTS RESERVED.

DIMENSION TOLERANCES UNLESS OTHERWISE SPECIFIED		Brandstrom Instruments
ANGLES $\pm 1^\circ$	2 PLACES $\pm .010$	
FRACTIONS $\pm 1/32$	3 PLACES $\pm .005$	
1 PLACE $\pm .015$	4 PLACES $\pm .0005$	
MATERIAL:	N/A	DRAWN:
FINISH:	N/A	CHECKED:
DATE:	SCALE: NONE	APPROVED:
TITLE:	SHUTTER ASSEMBLY	DWG NO: A0536
		SHEET: 1 OF 1